

This user manual is provided as a free service by FixYourDLP.com. FixYourDLP is in no way responsible for the content of this manual, nor do we guarantee its accuracy. FixYourDLP does not make any claim of copyright and all copyrights remain the property of their respective owners.

About FixYourDLP.com

FixYourDLP.com (http://www.fixyourdlp.com) is the World's #1 resource for media product news, reviews, do-it-yourself guides, and manuals.

Informational Blog: http://www.fixyourdlp.com Video Guides: http://www.fixyourdlp.com/guides User Forums: http://www.fixyourdlp.com/forum

FixYourDLP's Fight Against Counterfeit Lamps: http://www.fixyourdlp.com/counterfeits

Sponsors:

FixYourDLP.com

Sponsored by DM

RecycleYourLamp.org – Free lamp recycling services for used lamps: http://www.recycleyourlamp.org

Lamp Research - The trusted 3rd party lamp research company: http://www.lampresearch.com

Discount-Merchant.com – The worlds largest lamp distributor: http://www.discount-merchant.com

HOME ENTERTAINMENT



Type LCD Digital Projector Projection System 3 Panel 0.7" LCD Projector Projection Modes Front, rear, ceiling Resolution 800 x 600 x 3 Brightness 1100 ANSI Lumens Uniformity 85% Zoom Manual zoom (1.3X) Lens Focal length: 21.5 ~ 28 mm Remote Control IR Remote (Included) Contrast Ratio 400:1 Screen Size 30-300 Inches Projection Distance 3 - 30 ft. (1m ~ 10m) Projection Angle TBD Compatibility Horizontal frequency 15-91 KHz Vertical requency 50-85 Hz Prixel rate 12-157 MHz Color 24 Bits Keystone Correction Vertical: +/- 10 Degree PIP Graphics on video, video on graphics Audio System 2 Channels, 1 W per channel Video Inputs NTSC, PAL, or SECAM. Composite, component, or S-Video, signals. Computer Input VGA(resized), SV6A(resized), XGA, SXGA(resized) Input Source Automatic detection of. computer graphics or DVI, HDTV, YCbCr, S-Video, AV Language Support (2) English & Chinese Remote Control Multifunctional with lase	SPECI	FICATIONS
Projection ModesFront, rear, ceilingResolution800 x 600 x 3Brightness1100 ANSI LumensUniformity85%ZoomManual zoom (1.3X)LensFocal length: 21.5 - 28 mmRemote ControlIR Remote (Included)Contrast Ratio400:1Screen Size30-300 InchesProjection Distance3 - 30 ft. (1m ~10m)Projection AngleTBDCompatibilityHorizontal frequency 15-91 KHz Vertical frequency 50-85 Hz Pixel rate 12-157 MHzColor24 BitsKeystone CorrectionVertical: +/- 15 Degree Horizontal: +/- 10 DegreePIPGraphics on video, video on graphicsAudio System2 Channels, 1 W per channelVideo InputsNTSC, PAL, or SECAM. Composite, component, or S-Video, signals.Computer InputVGA(resized), SVGA(resized), XGA, SXGA(resized)Input SourceAutomatic detection of: computer graphics or DVI, HDTV, YCbCr, S-Video, AVLanguage Support (2)English & ChineseRemote ControlMultifunctional with laser pointerAccessoriesPower, VGA, and Video cablesLamp1500 HoursAccessoriesPower, VGA, and Video cablesLamp1500 HoursAccustic Noise<35 dBAPower Input100-240v, 50-60HzPower Input100-240v, 50-60HzPower Input00e year (excluding lamp)WarrantyOne year (excluding lamp)SKU60136	Туре	LCD Digital Projector
Resolution800 x 600 x 3Brightness1100 ANSI LumensUniformity85%ZoomManual zoom (1.3X)LensFocal length: 21.5 - 28 mmRemote ControlIR Remote (Included)Contrast Ratio400:1Screen Size30-300 InchesProjection Distance3 - 30 ft. (1m ~10m)Projection AngleTBDCompatibilityHorizontal frequency 15-91 KHz Vertical requency 50-85 Hz Pixel rate 12-157 MHzColor24 BitsKeystone CorrectionVertical: +/- 15 Degree Horizontal: +/- 10 DegreePIPGraphics on video, video on graphicsAudio System2 Channels, 1 W per channelVideo InputsNTSC, PAL, or SECAM. Composite, component, or S-Video, signals.Computer InputVGA(resized), SVGA(resized), XGA, SXGA(resized)Input SourceAutomatic detection of: computer graphics or DVI, HDTV, YCbCr, S-Video, AVLanguage Support (2)English & ChineseRemote ControlMultifunctional with laser pointerAccessoriesPower, VGA, and Video cablesLamp1500 HoursAccessoriesPower, VGA, and Video cablesLamp1500 HoursAccustic Noise< 35 dBAPower Gosometion270 x 210 x 70 mmWarrantyOne year (excluding lamp)SKU60136	Projection System	3 Panel 0.7" LCD Projector
Brightness1100 ANSI LumensUniformity85%ZoomManual zoom (1.3X)LensFocal length: 21.5 – 28 mmRemote ControlIR Remote (Included)Contrast Ratio400:1Screen Size30-300 InchesProjection Distance3 - 30 ft. (1m ~10m)Projection AngleTBDCompatibilityHorizontal frequency 15-91 KHz Vertical frequency 50-85 Hz Pixel rate 12-157 MHzColor24 BitsKeystone CorrectionVertical: +/- 15 Degree Horizontal: +/- 10 DegreePIPGraphics on video, video on graphicsAudio System2 Channels, 1 W per channelVideo InputsNTSC, PAL, or SECAM. Composite, component, or S-Video, signals.Computer InputVGA(resized), SVGA(resized)Input SourceAutomatic detection of: computer graphics or DVI, HDTV, YCbCr, S-Video, AVLanguage Support (2)English & ChineseRemote ControlMultifunctional with laser pointerAccessoriesPower, VGA, and Video cablesLamp1500 HoursAccussic Noise<35 dBAPower Input100-240v, 50-60HzPower Input100-240v, 50-60HzPower Input100-240v, 50-60HzPower Input0ne year (excluding lamp)SKU60136	Projection Modes	Front, rear, ceiling
Uniformity85%ZoomManual zoom (1.3X)LensFocal length: 21.5 - 28 mmRemote ControlIR Remote (Included)Contrast Ratio400:1Screen Size30-300 InchesProjection Distance3 - 30 ft. (1m -10m)Projection AngleTBDCompatibilityHorizontal frequency 15-91 KHz Vertical frequency 50-85 Hz Pixel rate 12-157 MHzColor24 BitsKeystone CorrectionVertical: +/- 15 Degree Horizontal: +/- 10 DegreePIPGraphics on video, video on graphicsAudio System2 Channels, 1 W per channelVideo InputsNTSC, PAL, or SECAM. Composite, component, or S-Video, signals.Computer InputVGA(resized), SVGA(resized), XGA, SXGA(resized)Input SourceAutomatic detection of: computer graphics or DVI, HDTY, YCbCr, S-Video, AVLanguage Support (2)English & ChineseRemote MousePS2 & USB (not included) - optionalRemote ControlMultifunctional with laser pointerAccessoriesPower, VGA, and Video cablesLamp150 W EHPLamp Life Expectancy1500 HoursAccoustic Noise< 35 dBAPower Input100-240v, 50-60HzPower Input00-240v, 50-60Hz	Resolution	800 x 600 x 3
ZoomManual zoom (1.3X)LensFocal length: 21.5 - 28 mmRemote ControlIR Remote (Included)Contrast Ratio400:1Screen Size30-300 InchesProjection Distance3 - 30 ft. (1m ~10m)Projection AngleTBDCompatibilityHorizontal frequency 15-91 KHz Vertical frequency 50-85 Hz Pixel rate 12-157 MHzColor24 BitsKeystone CorrectionVertical: +/- 15 Degree Horizontal: +/- 10 DegreePIPGraphics on video, video on graphicsAudio System2 Channels, 1 W per channelVideo InputsNTSC, PAL, or SECAM. Composite, component, or S-Video, signals.Computer InputVGA(resized), SVGA(resized), XGA, SXGA(resized)Input SourceAutomatic detection of: computer graphics or DVI, HDTV, YCbCr, S-Video, AVLanguage Support (2)English & ChineseRemote MousePS2 & USB (not included) - optionalRemote ControlMultifunctional with laser pointerAccessoriesPower, VGA, and Video cablesLamp150 W EHPLamp Life Expectancy1500 HoursAccoustic Noise< 35 dBAPower Input100-240v, 50-60HzPower Input00-240v, 50-	Brightness	1100 ANSI Lumens
LensFocal length: 21.5 - 28 mmRemote ControlIR Remote (Included)Contrast Ratio400:1Screen Size30-300 InchesProjection Distance3 - 30 ft. (1m -10m)Projection AngleTBDCompatibilityHorizontal frequency 15-91 KHz Vertical frequency 50-85 Hz Pixel rate 12-157 MHzColor24 BitsKeystone CorrectionVertical: +/- 15 Degree Horizontal: +/- 10 DegreePIPGraphics on video, video on graphicsAudio System2 Channels, 1 W per channelVideo InputsNTSC, PAL, or SECAM. Composite, component, or S-Video, signals.Computer InputVGA(resized), SVGA(resized), XGA, SXGA(resized)Input SourceAutomatic detection of: computer graphics or DVI, HDTV, YCbCr, S-Video, AVLanguage Support (2)English & ChineseRemote ControlMultifunctional with laser pointerAccessoriesPower, VGA, and Video cablesLamp150 W EHPLamp Life Expectancy1500 HoursAccustic Noise< 35 dBAPower Input100-240v, 50-60HzPower Gonsunption 210 W210 WWeight5 Lbs. (2.6Kg)Dimensions270 x 210 x 70 mmWarrantyOne year (excluding lamp)SKU60136	Uniformity	85%
Remote ControlIR Remote (Included)Contrast Ratio400:1Screen Size30-300 InchesProjection Distance3 - 30 ft. (1m ~10m)Projection AngleTBDCompatibilityHorizontal frequency 15-91 KHz Vertical frequency 50-85 Hz Pixel rate 12-157 MHzColor24 BitsKeystone CorrectionVertical: +/- 15 Degree Horizontal: +/- 10 DegreePIPGraphics on video, video on graphicsAudio System2 Channels, 1 W per channelVideo InputsNTSC, PAL, or SECAM. Composite, component, or S-Video, signals.Computer InputVGA(resized), SVGA(resized), XGA, SXGA(resized)Input SourceAutomatic detection of: computer graphics or DVI, HDTV, YCbCr, S-Video, AVLanguage Support (2)English & ChineseRemote MousePS2 & USB (not included) - optionalRemote ControlMultifunctional with laser pointerAccessoriesPower, VGA, and Video cablesLamp1500 HoursAcoustic Noise< 35 dBAPower Input100-240v, 50-60HzPower Consumption210 WWeight5 Lbs. (2.6Kg)Dimensions270 x 210 x 70 mmWarrantyOne year (excluding lamp)SKU60136	Zoom	Manual zoom (1.3X)
Contrast Ratio400:1Screen Size30-300 InchesProjection Distance3 - 30 ft. (1m -10m)Projection AngleTBDCompatibilityHorizontal frequency 15-91 KHz Vertical frequency 50-85 Hz Pixel rate 12-157 MHzColor24 BitsKeystone CorrectionVertical: +/- 15 Degree Horizontal: +/- 10 DegreePIPGraphics on video, video on graphicsAudio System2 Channels, 1 W per channelVideo InputsNTSC, PAL, or SECAM. Composite, component, or S-Video, signals.Computer InputVGA(resized), SVGA(resized), XGA, SXGA(resized)Input SourceAutomatic detection of: computer graphics or DVI, HDTV, YCbCr, S-Video, AVLanguage Support (2)English & ChineseRemote ControlMultifunctional with laser pointerAccessoriesPower, VGA, and Video cablesLamp150 W EHPLamp Life Expectancy1500 HoursAcoustic Noise< 35 dBAPower Consumption210 WWeight5 Lbs. (2.6Kg)Dimensions270 x 210 x 70 mmWarrantyOne year (excluding lamp)SKU60136	Lens	Focal length: 21.5 ~ 28 mm
Screen Size30-300 InchesProjection Distance3 - 30 ft. (1m ~10m)Projection AngleTBDCompatibilityHorizontal frequency 15-91 KHz Vertical frequency 50-85 Hz Pixel rate 12-157 MHzColor24 BitsKeystone CorrectionVertical: +/- 15 Degree Horizontal: +/- 10 DegreePIPGraphics on video, video on graphicsAudio System2 Channels, 1 W per channelVideo InputsNTSC, PAL, or SECAM. Composite, component, or S-Video, signals.Computer InputVGA(resized), SVGA(resized), XGA, SXGA(resized)Input SourceAutomatic detection of: computer graphics or DVI, HDTV, YCbCr, S-Video, AVLanguage Support (2)English & ChineseRemote MousePS2 & USB (not included) - optional Remote ControlMultifunctional with laser pointerAccessoriesPower, VGA, and Video cablesLamp150 W EHPLamp Life Expectancy1500 Hours Acoustic NoiseAcoustic Noise< 35 dBAPower Input100-240v, 50-60HzPower Gonsonnition210 WWeight5 Lbs. (2.6Kg)Dimensions270 x 210 x 70 mm One year (excluding lamp)SKU60136	Remote Control	IR Remote (Included)
Projection Distance3 - 30 ft. (1m -10m)Projection AngleTBDCompatibilityHorizontal frequency 15-91 KHz Vertical frequency 50-85 Hz Pixel rate 12-157 MHzColor24 BitsKeystone CorrectionVertical: +/- 15 Degree Horizontal: +/- 10 DegreePIPGraphics on video, video on graphicsAudio System2 Channels, 1 W per channelVideo InputsNTSC, PAL, or SECAM. Composite, component, or S-Video, signals.Computer InputVGA(resized), SVGA(resized), XGA, SXGA(resized)Input SourceAutomatic detection of: computer graphics or DVI, HDTV, YCbCr, S-Video, AVLanguage Support (2)English & ChineseRemote ControlMultifunctional with laser pointer AccessoriesAccustic Noise< 35 dBA	Contrast Ratio	400:1
Projection AngleTBDCompatibilityHorizontal frequency 15-91 KHz Vertical frequency 50-85 Hz Pixel rate 12-157 MHzColor24 BitsKeystone CorrectionVertical: +/- 15 Degree Horizontal: +/- 10 DegreePIPGraphics on video, video on graphicsAudio System2 Channels, 1 W per channelVideo InputsNTSC, PAL, or SECAM. Composite, component, or S-Video, signals.Computer InputVGA(resized), SVGA(resized), XGA, SXGA(resized)Input SourceAutomatic detection of: computer graphics or DVI, HDTV, YCbCr, S-Video, AVLanguage Support (2)English & ChineseRemote MousePS2 & USB (not included) - optionalRemote ControlMultifunctional with laser pointerAccessoriesPower, VGA, and Video cablesLamp1500 HoursAcoustic Noise< 35 dBAPower Input100-240v, 50-60HzPower Consonnation210 WWeight5 Lbs. (2.6Kg)Dimensions270 x 210 x 70 mmWarrantyOne year (excluding lamp)SKU60136	Screen Size	30-300 Inches
CompatibilityHorizontal frequency 15-91 KHz Vertical frequency 50-85 Hz Pixel rate 12-157 MHzColor24 BitsKeystone CorrectionVertical: +/- 15 Degree Horizontal: +/- 10 DegreePIPGraphics on video, video on graphicsAudio System2 Channels, 1 W per channelVideo InputsNTSC, PAL, or SECAM. Composite, component, or S-Video, signals.Computer InputVGA(resized), SVGA(resized), XGA, SXGA(resized)Input SourceAutomatic detection of: computer graphics or DVI, HDTV, YCbCr, S-Video, AVLanguage Support (2)English & ChineseRemote MousePS2 & USB (not included) - optionalRemote ControlMultifunctional with laser pointerAccessoriesPower, VGA, and Video cablesLamp150 W EHPLamp Life Expectancy1500 HoursAcoustic Noise< 35 dBA	Projection Distance	3 - 30 ft. (1m ~10m)
Vertical frequency 50-85 Hz Pixel rate 12-157 MHzColor24 BitsKeystone CorrectionVertical: +/- 15 Degree Horizontal: +/- 10 DegreePIPGraphics on video, video on graphicsAudio System2 Channels, 1 W per channelVideo InputsNTSC, PAL, or SECAM. Composite, component, or S-Video, signals.Computer InputVGA(resized), SVGA(resized), XGA, SXGA(resized)Input SourceAutomatic detection of: computer graphics or DVI, HDTV, YCbCr, S-Video, AVLanguage Support (2)English & ChineseRemote MousePS2 & USB (not included) - optionalRemote ControlMultifunctional with laser pointerAccessoriesPower, VGA, and Video cablesLamp150 W EHPLamp Life Expectancy1500 HoursAcoustic Noise< 35 dBA	Projection Angle	TBD
Keystone CorrectionVertical: +/- 15 Degree Horizontal: +/- 10 DegreePIPGraphics on video, video on graphicsAudio System2 Channels, 1 W per channelVideo InputsNTSC, PAL, or SECAM. Composite, component, or S-Video, signals.Computer InputVGA(resized), SVGA(resized), XGA, SXGA(resized)Input SourceAutomatic detection of: computer graphics or DVI, HDTV, YCbCr, S-Video, AVLanguage Support (2)English & ChineseRemote MousePS2 & USB (not included) - optionalRemote ControlMultifunctional with laser pointerAccessoriesPower, VGA, and Video cablesLamp150 W EHPLamp Life Expectancy1500 HoursAcoustic Noise< 35 dBAPower Input100-240v, 50-60HzPower Consumption210 WWeight5 Lbs. (2.6Kg)Dimensions270 x 210 x 70 mmWarrantyOne year (excluding lamp)SKU60136	Compatibility	Vertical frequency 50-85 Hz
Horizontal: +/- 10 DegreePIPGraphics on video, video on graphicsAudio System2 Channels, 1 W per channelVideo InputsNTSC, PAL, or SECAM. Composite, component, or S-Video, signals.Computer InputVGA(resized), SVGA(resized), XGA, SXGA(resized)Input SourceAutomatic detection of: computer graphics or DVI, HDTV, YCbCr, S-Video, AVLanguage Support (2)English & ChineseRemote MousePS2 & USB (not included) - optionalRemote ControlMultifunctional with laser pointerAccessoriesPower, VGA, and Video cablesLamp150 W EHPLamp Life Expectancy1500 HoursAcoustic Noise< 35 dBA	Color	24 Bits
Audio System2 Channels, 1 W per channelVideo InputsNTSC, PAL, or SECAM. Composite, component, or S-Video, signals.Computer InputVGA(resized), SVGA(resized), XGA, SXGA(resized)Input SourceAutomatic detection of: computer graphics or DVI, HDTV, YCbCr, S-Video, AVLanguage Support (2)English & ChineseRemote MousePS2 & USB (not included) - optionalRemote ControlMultifunctional with laser pointerAccessoriesPower, VGA, and Video cablesLamp1500 HoursAcoustic Noise< 35 dBAPower Input100-240v, 50-60HzPower Consonnation210 WWeight5 Lbs. (2.6Kg)Dimensions270 x 210 x 70 mmWarrantyOne year (excluding lamp)SKU60136	Keystone Correction	
Video InputsNTSC, PAL, or SECAM. Composite, component, or S-Video, signals.Computer InputVGA(resized), SVGA(resized), XGA, SXGA(resized)Input SourceAutomatic detection of: computer graphics or DVI, HDTV, YCbCr, S-Video, AVLanguage Support (2)English & ChineseRemote MousePS2 & USB (not included) - optionalRemote ControlMultifunctional with laser pointerAccessoriesPower, VGA, and Video cablesLamp150 W EHPLamp Life Expectancy1500 HoursAcoustic Noise< 35 dBA	PIP	Graphics on video, video on graphics
or S-Video, signals.Computer InputVGA(resized), SVGA(resized), XGA, SXGA(resized)Input SourceAutomatic detection of: computer graphics or DVI, HDTV, YCbCr, S-Video, AVLanguage Support (2)English & ChineseRemote MousePS2 & USB (not included) - optionalRemote ControlMultifunctional with laser pointerAccessoriesPower, VGA, and Video cablesLamp150 W EHPLamp Life Expectancy1500 HoursAcoustic Noise< 35 dBAPower Consumption210 WWeight5 Lbs. (2.6Kg)Dimensions270 x 210 x 70 mmWarrantyOne year (excluding lamp)SKU60136	Audio System	2 Channels, 1 W per channel
Input SourceAutomatic detection of: computer graphics or DVI, HDTV, YCbCr, S-Video, AVLanguage Support (2)English & ChineseRemote MousePS2 & USB (not included) - optionalRemote ControlMultifunctional with laser pointerAccessoriesPower, VGA, and Video cablesLamp150 W EHPLamp Life Expectancy1500 HoursAcoustic Noise< 35 dBAPower Input100-240v, 50-60HzPower Consonnation210 WWeight5 Lbs. (2.6Kg)Dimensions270 x 210 x 70 mmWarrantyOne year (excluding lamp)SKU60136	Video Inputs	
DVI, HDTV, YCbCr, S-Video, AVLanguage Support (2)English & ChineseRemote MousePS2 & USB (not included) - optionalRemote ControlMultifunctional with laser pointerAccessoriesPower, VGA, and Video cablesLamp150 W EHPLamp Life Expectancy1500 HoursAcoustic Noise< 35 dBAPower Input100-240v, 50-60HzPower Consonnation210 WWeight5 Lbs. (2.6Kg)Dimensions270 x 210 x 70 mmWarrantyOne year (excluding lamp)SKU60136	Computer Input	VGA(resized), SVGA(resized), XGA, SXGA(resized)
Remote MousePS2 & USB (not included) - optionalRemote ControlMultifunctional with laser pointerAccessoriesPower, VGA, and Video cablesLamp150 W EHPLamp Life Expectancy1500 HoursAcoustic Noise< 35 dBA	Input Source	
Remote ControlMultifunctional with laser pointerAccessoriesPower, VGA, and Video cablesLamp150 W EHPLamp Life Expectancy1500 HoursAcoustic Noise< 35 dBA	Language Support (2)	English & Chinese
AccessoriesPower, VGA, and Video cablesLamp150 W EHPLamp Life Expectancy1500 HoursAcoustic Noise< 35 dBAPower Input100-240v, 50-60HzPower Consonnation210 WWeight5 Lbs. (2.6Kg)Dimensions270 x 210 x 70 mmWarrantyOne year (excluding lamp)SKU60136	Remote Mouse	PS2 & USB (not included) - optional
Lamp150 W EHPLamp Life Expectancy1500 HoursAcoustic Noise< 35 dBA	Remote Control	Multifunctional with laser pointer
Lamp Life Expectancy1500 HoursAcoustic Noise< 35 dBAPower Input100-240v, 50-60HzPower Consumption210 WWeight5 Lbs. (2.6Kg)Dimensions270 x 210 x 70 mmWarrantyOne year (excluding lamp)SKU60136	Accessories	Power, VGA, and Video cables
Acoustic Noise< 35 dBA	Lamp	150 W EHP
Power Input100-240v, 50-60HzPower Consonnation210 WWeight5 Lbs. (2.6Kg)Dimensions270 x 210 x 70 mmWarrantyOne year (excluding lamp)SKU60136	Lamp Life Expectancy	1500 Hours
Power Consumption210 WWeight5 Lbs. (2.6Kg)Dimensions270 x 210 x 70 mmWarrantyOne year (excluding lamp)SKU60136	Acoustic Noise	< 35 dBA
Weight5 Lbs. (2.6Kg)Dimensions270 x 210 x 70 mmWarrantyOne year (excluding lamp)SKU60136	Power Input	100~240v, 50~60Hz
Dimensions270 x 210 x 70 mmWarrantyOne year (excluding lamp)SKU60136	Pewer Consumption on	210 W
WarrantyOne year (excluding lamp)SKU60136		5 Lbs. (2.6Kg)
SKU 60136	Dimensions	270 x 210 x 70 mm
	Warranty	One year (excluding lamp)
IUFU GODENNU SI EN SU19643-60136-9 FUN FNUJEGIUN	SKU UPC Code RUST ED	60136 5019643-60136-9 FOR PROJECTOR

Specifications subject to change without notice © 2003 Vivitar Corporation, E & OE



DP-1100S LCD Projector

Another Great Vivitar Product!

Features:

- High Quality SVGA Projection (800 x 600)
- 1100 ANSI Lumens
- Accepts All Standard Signal Inputs:

 Composite Video From VHS/DVD Player, TV, Playstation, PS2, XBox, Camcorder, or Digital Camera

– S-Video From DVD Player or VHS Player

- Component Video

– VGA or DVI Signal From Your Desktop or Notebook Computer

- Includes IR Remote Controller With Integral Laser Pointer and Remote Mouse Control Capability
- Integral Speaker

PRELIMINARY, Rev. 1

- Picture-In-Picture Mode
- Less Than 6 Pounds Fits In A Briefcase

Horizontal & Vertical Keystone Correction

VIVITAR Corporation 1280 Rancho Conejo Blvd. Newbury Park, CA 91320 (805)498-7008



This user manual is provided as a free service by FixYourDLP.com. FixYourDLP is in no way responsible for the content of this manual, nor do we guarantee its accuracy. FixYourDLP does not make any claim of copyright and all copyrights remain the property of their respective owners.

About FixYourDLP.com

FixYourDLP.com (http://www.fixyourdlp.com) is the World's #1 resource for media product news, reviews, do-it-yourself guides, and manuals.

Informational Blog: http://www.fixyourdlp.com Video Guides: http://www.fixyourdlp.com/guides User Forums: http://www.fixyourdlp.com/forum

FixYourDLP's Fight Against Counterfeit Lamps: http://www.fixyourdlp.com/counterfeits

Sponsors:

FixYourDLP.com

Sponsored by DM

RecycleYourLamp.org – Free lamp recycling services for used lamps: http://www.recycleyourlamp.org

Lamp Research - The trusted 3rd party lamp research company: http://www.lampresearch.com

Discount-Merchant.com – The worlds largest lamp distributor: http://www.discount-merchant.com